

No.9, Industrial Road, Kuan Tien District, Tainan City, Taiwan, R.O.C. Tel : 886-6-6986623 Fax : 886-6-6990272 Web Site : www.ckm.com.tw E-Mail : ckm@mail.ckm.com.tw

TECHINCAL DATA SHEET

Date: August 01, 2011

CKM LDT700 Features: • Production procedure is under an ISO 9001 approved environment and meet or exceed ASTM C635 standards. · Cost control, global compatibility and availability.

· Maximum economy and design simplicity.

- · Cross tee overlap ends resist twisting and reinforced twist resistant overlap connector clips.
- · Main Runner loading capacity meets 14.14kg/m.

Applications:

General:

Offices, education, retail, hospital, galleries, large areas.

ASTM C635 classification, commercial-quality hot dipped galvanized steel. Exposed surface chemically cleaned, galvanized steel capping prepainted in baked polyester paint.

Mainrunner	Description	Length	Height (mm)	Width (mm)	Thickness (mm)	Pcs/Carton	4'(1.2M) Hanger Spacing	Class
	Double-web construction, web height 1-1/2" (38mm)	12'	38	24	0.31	25	12.73kg/M	ASTM Light Duty
24	and 15/16" (24mm) bottom flange with prepainted steel.	3.6M	38	24	0.31	25	12.73kg/M	

Cross Tee		Description	Length	Height (mm)	Width (mm)	Thickness (mm)	Pcs/Carton	4'(1.2M) Hanger Spacing	Class
	overlap at each end.	4'	28	24	0.31	50			
		2'	28	24	0.31	75			
		1.2M	28	24	0.31	50			
		0.6M	28	24	0.31	75			

L Wall Angle	Description	Length	Height (mm)	Width (mm)	Thickness (mm)	Pcs/Carton	4'(1.2M) Hanger Spacing	
24	With prepainted steel	10'	24	24	0.4	40		
		3.0M	24	24	0.4	40		

Physical Data:

Color

CKM standard polyester white or Black color.

Material

Body: Double web, hot-dipped galvanized steel. Steel's galvanizing specification to Z06~Z08 as per JIS standard. Cap: Pre-painted hot dipped galvanized steel.

Installation

with ASTM C636

Loading Capacity

Must be installed in accordance System meets or exceeds load 10'(3.0M) mainrunner compliance specification per ASTM C635. Mainrunner will not deflect more than 1/8" over available in CKM. 48" span (or 1/360) in Light Duty, Intermediate Duty or heavy Duty categories.

Notes

and 12'(3.6M)Wall angle are also